



PART DETAILS			
ITEM NUMBER	STOCK NUMBER	DESCRIPTION	COMMENTS
1	AQ21	Schlegel Aquamac Perimeter Seal	
2	Doorstop 30mm x18mm FRR	Finger Joint Pine =450 kg/m ³ Door Stop	
3	J1 FRR	J1 Jamb 30mm Hardwood,(Minimum Density =650 kg/m ³)	
4	IS Mastic	Infernoguard Liquid Application Mastic	Mastic to nominal 25mm depth
5	PEF Rod	Polyurethane Foam Backing Rod	Diameter to suit gap width
6	WB	Wedging Block	Cut to suit
7	Wood Screws	75mm x 10g Wood Screw	Refer to install instructions for fixing points
8	Wood Screws	70mm x 10g CSK TEK	Refer to install instructions for fixing points
9	N30 x 3.2MM	Jolthead Nail 30mm	200 crs Typical

Specifications	
Core	Infernoguard 60
FRR	-/60/60sm, -/60/30sm, -/60/-sm
Wall	Korok
Jamb	J1 (FRR)

Drawn	G . STABLES	 SOTERIA DOORS Innovative Openings	Edward Street Dargaville 0310 Ph.: 0508 966 378	
Client	Soteria Doors			
Job	-			
Drawing Type	Installation	J1 Fire Resistance Rated Jamb - Korok Wall Installation		
Date	24/9/2024			
ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE STATED		 3rd ANGLE PROJECTION	Drawing No. J1 FRR60 K	
TOLERANCES UNLESS OTHERWISE STATED: LINEAR: X - ±2 HOLES: ±0.1 X.X - ±0.1 ANGULAR: X.X - ±0.1° X.XX - ±0.05			Revision A3	Sheet No. 1 / 1
		© COPYRIGHT		